

**XF1 INTEGRA 160 Race****TECHNICAL SPECIFICATIONS**

Moteur	Motor	Motor	Motore	Brose S-Mag 36 Volt, Max power: 250 Watt, Torque/Coppla: 90 Nm
Batterie	Batterie	Battery	Batteria	Fantic Integra, Lithium Ion, 36 Volt, 630Wh
Display	Display	Display	Display	Brose-Marquardt multifunctional display & push-assistance selection unit
Cadre & Tailles	Rahmen	Frame	Telalo	Aluminium Enduro frame, CNC parts, Sizes: S - M - L
Fourche	Gabel	Fork	Forcella	RockShox Lyrik Select+ 29" 160mm
Amortisseur	Dämpfer	Shock	Ammortizzatore	RockShox SuperDeluxe Select+ , T205-60 Air
Groupe	Schaltung	Groupset	Cambio	Sram GX e-click Eagle 12V
Pédaller	Fahrrad kurbel	Crankset	Guarnitura	FSA Isis 165mm
Cassette	Schalnkassette	Cassette	Pignoni	SunRace MX90-W 11-50 - 12V - Silver Red
Chaîne	Kette	Chain	Catena	Sram NX Eagle 12V
Freins avant	Vorderradbremse	Front brake	Freno ant.	Sram CODE R, 4P, Hydraulic Disc Brake, 203mm disc steel
Freins arrière	Hinterradbremse	Rear brake	Freno post.	Sram CODE R, 4P, Hydraulic Disc Brake, 203mm disc steel
Pneus	Reifen	Tires	Pneumatici	Maxxis Minion, front DHF 29" X 2.5 - rear DHR II 27.5" X 2.6 TLE
Jantes & Rayons	Felgen und Spelchen	Wheels	Cerchi e raggi	Mavic E-XA , ASY Straight Pull , front Ø29"c.28 - rear Ø27.5" c.35 - T.Ready
Moyeux avt	Vorderradnabe	Front hub	Mozzo ant.	MAVIC 110 mm Boost thru axle 15mm
Moyeux arr	Hinterradnabe	Rear hub	Mozzo post.	MAVIC 148 mm Boost thru axle 12mm
Guidon	Lenker	Handlebar	Manubrio	FSA Grid 760mm, oversize, Rise 15
Potence	Vorbau	Stem	Attacco manubrio	FSA Grid 50mm, oversize
Tige de selle	Sattelstütze	Seatpost	Tubo sella	Switch, height-adjustable dropper (telescopico), S-M(100mm), L(125mm)
Selle	Sattel	Saddle	Sella	Sellelalla X-LR Gel Flow